

Datum: 24.05.2026



## 3/2 ventil »FUTURA«, Elektr. voden, 24 V AC, Velikost 2, G 1/2

Kategorija: [3/2-way valve, electrically operated, 24 V AC](#)Šifra: **156609RIE**

(slika je simbolična)

### Kratek opis

3/2-way valve »FUTURA«, electr. actuated with solenoid 24 V AC, 50 Hz, Size 2, G 1/2, Exhaust G 1/2, Input pressure 2 - 10 bar

Pneumatic systems or parts of systems can be switched on and off by means of an electrical signal.

3/2-way type including silencer.

When they are switched off, the system is exhausted at the same time.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Električni priključek	Socket coupling EN 175301-803, form C, poles 2+PE
IP zaščita	IP 65
Izpušni zrak	G 1/2 At $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Merjenje pretoka	bar
Navoj	G 1/2
Ohišje	PA66 GF60
Priključni navoj	Material: Die-cast zinc
Serijska	FUTURA
Srednje	Compressed air, neutral gases
Zaklepna moč pri 50 Hz AC napetosti [VA]	1.6
Min. vhodni tlak [bar]	2
Velikost	2
Dvižna moč pri 50 Hz AC napetosti [VA]	2.2
Vhodna moč	2.5 Watt with DC voltage
Max. vhodni tlak [bar]	10
Max. temperaturno območje [°C]	50
A [mm]	63.0
C [mm]	93.8
Delovni cikel [%]	100
B [mm]	150.3
Pretok [l/min]	4500