



(slika je simbolična)

3/2 ventil »FUTURA-mali«, Elektr. voden, 115 V AC, G 1/4

Kategorija: [3/2-way valve, electrically operated, 115 V AC](#)Šifra: **142523RIE**

Kratek opis

3/2-way valve »FUTURA-mini«, electr. actuated with solenoid 115 V AC, 50 Hz, Size 0, G 1/4, Exhaust G 1/4, Input press. 2.5-10 bar

Pneumatic systems or parts of systems can be switched on and off by means of an electrical signal.

3/2-way type including silencer.

When they are switched off, the system is exhausted at the same time.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Električni priključek	Socket coupling EN 175301-803, form C, poles 2+PE
IP zaščita	IP 65
Izpušni zrak	G 1/4 At $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Merjenje pretoka	bar
Navoj	G 1/4
Ohišje	PA66 GF60
Priključni navoj	Plastic
Serijska	FUTURA-mini
Srednje	Compressed air, neutral gases
Zaklepna moč pri 50 Hz AC napetosti [VA]	1.6
Dvižna moč pri 50 Hz AC napetosti [VA]	2.2
Min. vhodni tlak [bar]	2.5
Vhodna moč	2.5 Watt with DC voltage
Max. vhodni tlak [bar]	10
A [mm]	43.0
Max. temperaturno območje [°C]	50
C [mm]	93.0
Delovni cikel [%]	100
B [mm]	138.0
Pretok [l/min]	2000