



## 3/2 ventil »FUTURA«, pnevmatsko voden, Velikost 1, G 3/8

Kategorija: [3/2-way valves, pneumatically operated](#)  
Šifra: **156617RIE**

(slika je simbolična)

### Kratek opis

3/2-way valve »FUTURA«, pneumatically actuated, Size 1, G 3/8, Exhaust G 1/4, Input pressure max. 16 bar, Temp. -10 °C to 50 °C

Pneumatic systems or parts of systems can be switched on and off by means of an pneumatic signal.  
3/2-way type including silencer.

When they are switched off, the system is exhausted at the same time.

### Tehnične Specifikacije

|                                |  |
|--------------------------------|--|
| Min. temperaturno območje [°C] | -10  |
| Izpušni zrak                   | G 1/4<br>At $P_2 = 6$ bar and<br>pressure drop $\Delta p = 1$<br>bar |
| Merjenje pretoka               | G 3/8<br>PA66 GF60   |
| Navoj                          | Material: Die-cast zinc  |
| Ohišje                         | FUTURA   |
| Priključni navoj               | Compressed air,<br>neutral gases                                     |
| Serijska                       | 1  |
| Srednje                        | 16   |
| Velikost                       | 50   |
| Max. vhodni tlak [bar]         | 52.0   |
| Max. temperaturno območje [°C] | 52.1   |
| A [mm]                         | 85.1   |
| C [mm]                         | 2000   |
| B [mm]                         |  |
| Pretok [l/min]                 |  |