



(slika je simbolična)

## **3/2 Vklopni ventil »G«, 24 V DC, Velikost 300, G 1/2**

Kategorija: [Start-up valve, power supply 24 V DC](#)  
Šifra: **116349RIE**

### **Kratek opis**

3/2-way start-up valve »G«, 24 V DC, with mounting bracket and silencer, Size 300, G 1/2, Input pressure 2.5 - 9 bar Combined shut-off and pressure build-up valve (start-up valve). Operated by secondary pressure for controlled pressurisation of pneumatic systems.

The 3/2-way valve opens when the solenoid is activated. The full cross-section of the valve is open when the working pressure is 50% of the input pressure. When the solenoid is deactivated, the 3/2-way valve closes and the pressure in the line is exhausted via the regulator. With adjustable restrictor.

### **Tehnične Specifikacije**

Električni priključek	Device plug PG 9, type B
Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 1/2
Ohišje	Die-cast aluminium
Serijska	G
Tesnilo	NBR
Min. vhodni tlak [bar]	2.5
Max. vhodni tlak [bar]	9
D [mm]	34.0
A [mm]	65.0
Max. sobna temperatura [°C]	70
Max. temperatura medija [°C]	70
C [mm]	97.0
B [mm]	131.0
Velikost	300
Pretok [l/min]	2500