

Datum: 07.06.2026



(slika je simbolična)

## 3/2 Vklopni ventil »G«, 24 V DC, Velikost 400, G 1/2

Kategorija: [Start-up valve, power supply 24 V DC](#)  
Šifra: **116353RIE**

### Kratek opis

3/2-way start-up valve »G«, 24 V DC, with mounting bracket and silencer, Size 400, G 1/2, Input pressure 2.5 - 9 bar Combined shut-off and pressure build-up valve (start-up valve). Operated by secondary pressure for controlled pressurisation of pneumatic systems.

The 3/2-way valve opens when the solenoid is activated. The full cross-section of the valve is open when the working pressure is 50% of the input pressure. When the solenoid is deactivated, the 3/2-way valve closes and the pressure in the line is exhausted via the regulator. With adjustable restrictor.

### Tehnične Specifikacije

|                              |  |
|------------------------------|--|
| Električni priključek        | Device plug PG 9, type B   |
| Merjenje pretoka             | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj                        | G 1/2  |
| Ohišje                       | Die-cast aluminium   |
| Serijska                     | G  |
| Tesnilo                      | NBR  |
| Min. vhodni tlak [bar]       | 2.5  |
| Max. vhodni tlak [bar]       | 9  |
| D [mm]                       | 40.5   |
| Max. sobna temperatura [°C]  | 70   |
| Max. temperatura medija [°C] | 70   |
| A [mm]                       | 78.0   |
| C [mm]                       | 102.0  |
| B [mm]                       | 142.5  |
| Velikost                     | 400  |
| Pretok [l/min]               | 4500   |