



(slika je simbolična)

3/2 Vklopni ventil »G-mali«, 230 V AC/50 Hz, Velikost 200, G 1/4

Kategorija: [Start-up valve, power supply 230 V AC, 50 Hz](#)
Šifra: **116342RIE**

Kratek opis

3/2-way start-up valve »G-mini«, 230 V AC / 50 Hz, with mounting bracket and silencer, Size 200, G 1/4, Input pressure 2.5 - 9 bar

Combined shut-off and pressure build-up valve (start-up valve). Operated by secondary pressure for controlled pressurisation of pneumatic systems.

The 3/2-way valve opens when the solenoid is activated.

The full cross-section of the valve is open when the working pressure is 50% of the input pressure. When the solenoid is deactivated, the 3/2-way valve closes and the pressure in the line is exhausted via the regulator. With adjustable restrictor.

Tehnične Specifikacije

| | |
|------------------------------|--|
| Električni priključek | Device plug PG 9, type B |
| Merjenje pretoka | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj | G 1/4 |
| Ohišje | Die-cast aluminium |
| Serija | GA-mini |
| Tesnilo | NBR |
| Min. vhodni tlak [bar] | 2.5 |
| Max. vhodni tlak [bar] | 9 |
| D [mm] | 30.0 |
| A [mm] | 59.0 |
| Max. sobna temperatura [°C] | 70 |
| Max. temperatura medija [°C] | 70 |
| C [mm] | 93.5 |
| B [mm] | 123.5 |
| Velikost | 200 |
| Pretok [l/min] | 550 |