

Datum: 01.07.2026



(slika je simbolična)

5/2-potni ventil, NAMUR, monostabilen, G 1/4, 230 V, 50Hz

Kategorija: [5/2-way spool valve with NAMUR style interface](#)
Šifra: **103661RIE**

Kratek opis

5/2-way valve, NAMUR, Anodised aluminium, Temp. -20 °C to 70 °C, Working pressure 1.5 - 10 bar, Connection G 1/4, 230 V, 50Hz
3/2 and 5/2-way spool valves, monostable, with air purging function and pneumatic spring return.
With latching manual operator and optional outgoing air restriction.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Električni priključek	Connector socket Pg 9 Plug connector PG 9, 1 coding pin, 2 Orings, 2 fixing screws
Obseg dobave	Aluminium anodised G 1/4 latching Air, neutral gases (filtered)
Ohišje	NBR
Povezava	Stainless steel
Ročno upravljanje	1.5
Srednje	3 W= / 5 VA~
Tesnilo	7
Tuljava	10
Min. delovni tlak [bar]	70
Vhodna moč	
DN	
Max. delovni tlak [bar]	
Max. delovna temperatura [°C]	
Napetost	230 V, 50 Hz
Pretok [l/min]	1250