

Datum: 21.04.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si

(slika je simbolična)

5/2-potni ventil, NAMUR, monostabilen, G 1/4, 24 V DC

Kategorija: [5/2-way spool valve with NAMUR style interface](#)
Šifra: **103662RIE**

Kratek opis

5/2-way valve, NAMUR, Anodised aluminium, Temp. -20 °C to 70 °C, Working pressure 1.5 - 10 bar, DN 7, Connection G 1/4, 24 V DC
3/2 and 5/2-way spool valves, monostable, with air purging function and pneumatic spring return.
With latching manual operator and optional outgoing air restriction.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Električni priključek	Connector socket Pg 9 Plug connector PG 9, 1 coding pin, 2 Orings, 2 fixing screws
Obseg dobave	Aluminium anodised
Ohišje	G 1/4
Povezava	latching
Ročno upravljanje	Air, neutral gases (filtered)
Srednje	NBR
Tesnilo	Stainless steel
Tuljava	1.5
Min. delovni tlak [bar]	3 W=/ 5 VA~
Vhodna moč	7
DN	10
Max. delovni tlak [bar]	24 V DC
Napetost	70
Max. delovna temperatura [°C]	1250
Pretok [l/min]	