

Active charcoal filter with differential pressure gauge, G 1/2

Kategorija: [Activated carbon filter with differential pressure gauge](#)
Šifra: **199821RIE**

(slika je simbolična)

Kratek opis

Active charcoal filter with differential pressure gauge, 0.003 mg/m³, G 1/2, Input pressure 4 - 16 bar, Temp. 1.5 °C to 80 °C

For adsorbing vaporous media.

A micro-filter must be connected upstream if dried air is not available.

Tehnične Specifikacije

Element filtra	non-woven medium, impregnated with activated carbon
Merjenje pretoka	At P ₁ = 7 bar and pressure drop Δ _p = 0.1 bar
Navoj	G 1/2
Ohišje	Aluminium
Posoda filtra	Aluminium
Rang filtra [μm]	0.00
Vsebnost olja v ostanku [mg/m ³]	0.003
Min. sobna temperatura [°C]	1.5
Min. temperatura medija [°C]	1.5
Max. označeni razpon diferencialnega manometra [bar]	2
Max. vhodni tlak [bar]	16
C [mm]	28.0
Max. sobna temperatura [°C]	80
Max. temperatura medija [°C]	80
Učinkovitost [%]	99.9999
A [mm]	104.0
D [mm]	399.0
Pretok [l/min]	1500