

Active charcoal filter with differential pressure gauge, G 3/4



Kategorija: [Activated carbon filter with differential pressure gauge](#)
Šifra: **199823RIE**

(slika je simbolična)

Kratek opis

Active charcoal filter with differential pressure gauge, 0.003 mg/m³, G 3/4, Input pressure 4 - 16 bar, Temp. 1.5 °C to 80 °C

For adsorbing vaporous media.

A micro-filter must be connected upstream if dried air is not available.

Tehnične Specifikacije

| | |
|--|--|
| Element filtra | non-woven medium, impregnated with activated carbon |
| Merjenje pretoka | At P ₁ = 7 bar and pressure drop Δ _p = 0.1 bar |
| Navoj | G 3/4 |
| Ohišje | Aluminium |
| Posoda filtra | Aluminium |
| Rang filtra [μm] | 0.00 |
| Vsebnost olja v ostanku [mg/m ³] | 0.003 |
| Min. sobna temperatura [°C] | 1.5 |
| Min. temperatura medija [°C] | 1.5 |
| Max. označeni razpon diferencialnega manometra [bar] | 2 |
| Max. vhodni tlak [bar] | 16 |
| C [mm] | 28.0 |
| Max. sobna temperatura [°C] | 80 |
| Max. temperatura medija [°C] | 80 |
| Učinkovitost [%] | 99.9999 |
| A [mm] | 104.0 |
| D [mm] | 399.0 |
| Pretok [l/min] | 3666 |