

Ball valve standard type, IT/ET, nickel-plated brass, G 1/4



Kategorija: [Ball valve with butterfly handle black, standard type, IT/ET thread](#)
Šifra: **129146RIE**

(slika je simbolična)

Kratek opis

Ball valve, Butterfly handle black, Standard type, IT/ET, nickel-plated brass, Operat. temp. -20 bis 150 °C, G 1/4, PN max. 50 bar

Applications: Compressed air, water, non-toxic and non-corrosive gases, heating systems and air conditioning systems.

Tehnične Specifikacije

| | |
|---------------------|--|
| Delovna temperatura | -20 °C to 150 °C (no steam) |
| Krogelno tesnilo | PTFE |
| Krogla | Chrome-plated brass |
| Material | Nickel-plated brass |
| Material navojev | Bright brass |
| Navoj | G 1/4 |
| Ročica - metuljček | Aluminium, painted black |
| Standardni navoj | G-thread acc. to DIN EN ISO 228-1, tolerance class B |
| Stebelno tesnilo | NBR / FKM (Seal package consists of 2 O-rings) |
| DN | 8 |
| F [mm] | 10.0 |
| E [mm] | 10.5 |
| B [mm] | 37.0 |
| A [mm] | 47.0 |
| PN [bar] | 50 |
| L [mm] | 54.0 |