**TRG d.o.o.**
**Celovška cesta 150, 1000 Ljubljana**

**Davčna št.:** SI 56119488
**Telefon:** 01 500 14 42
**E-mail:** info@podjetje-trg.si
**WWW:** www.www.karcher-trg.si

**Datum:** 07.11.2026

# Ball valve standard type, IT/IT, nickel-plated brass, G 3/8



Kategorija: Ball valve with hand lever black, standard type, IT/IT thread
Šifra: **129123RIE**

(slika je simbolična)

## Kratek opis

Ball valve, Manual lever black, Standard type., IT/IT, nickel-plated brass, Operating temp. -20 bis 150 °C, G 3/8, PN max. 50 bar
Applications: Compressed air, water, non-toxic and non-corrosive gases, heating systems and air conditioning systems.

## Tehnične Specifikacije

| | |
|---|---|
| Delovna temperatura | -20 °C to 150 °C (no steam) |
| Krogelno tesnilo | PTFE |
| Krogla | Chrome-plated brass |
| Material | Nickel-plated brass |
| Material navojev | Nickel-plated brass |
| Navoj | G 3/8 |
| Ročica | Galvanised steel, painted black |
| Standardni navoj | G-thread acc. to DIN EN ISO 228-1, tolerance class B |
| Stebelno tesnilo | NBR / FKM (Seal package consists of 2 O-rings) |
| DN | 10 |
| E [mm] | 10.0 |
| F [mm] | 10.0 |
| B [mm] | 37.0 |
| L [mm] | 44.4 |
| PN [bar] | 50 |
| A [mm] | 80.0 |