

Ball valve standard type, IT/IT, nickel-plated brass, G 3



Kategorija: [Ball valve with hand lever black, standard type, IT/IT thread](#)
Šifra: **129131RIE**

(slika je simbolična)

Kratek opis

Ball valve, Manual lever black, Standard type., IT/IT, nickel-plated brass, Operating temp. -20 bis 150 °C, G 3, PN max. 16 bar
Applications: Compressed air, water, non-toxic and non-corrosive gases, heating systems and air conditioning systems.

Tehnične Specifikacije

| | |
|---------------------|--|
| Delovna temperatura | -20 °C to 150 °C (no steam) |
| Krogelno tesnilo | PTFE |
| Krogla | Chrome-plated brass |
| Material | Nickel-plated brass |
| Material navojev | Nickel-plated brass |
| Navoj | G 3 |
| Ročica | Galvanised steel, painted black |
| Standardni navoj | G-thread acc. to DIN EN ISO 228-1, tolerance class B |
| Stebelno tesnilo | NBR / FKM (Seal package consists of 2 O-rings) |
| PN [bar] | 16 |
| E [mm] | 26.0 |
| F [mm] | 26.0 |
| DN | 80 |
| B [mm] | 133.0 |
| L [mm] | 157.0 |
| A [mm] | 250.0 |