



(slika je simbolična)

Bidirectional flow control valve, both directions, G1/4, plug-in 6

Kategorija: [Bidirectional flow control valve, both directions B](#)
Šifra: **116958RIE**

Kratek opis

Bidirectional flow control valve, both dir. (B), knurled screw, G1/4, plug-in 6, rotating, 0 to 10 bar, -20 °C to 80 °C, nickel-plated brass

For throttling flow rates and regulating the piston speed of cylinders. Small dimensions, ideal for tight spaces. To be screwed directly into the valve or cylinder. The set flow rate can be locked via the lock nut in the version with knurled screw. The variants in banjo bolt construction can be rotated during assembly and are fixed after tightening. The variants with plug-in connector, rotated can also be rotated freely after assembly. The seals and lubricants used are silicone-free.

Tehnične Specifikacije

| | |
|--------------------------------|--------------------------------|
| Min. temperaturno območje [°C] | -20 |
| Design | rotating |
| Ffunkcija | Both directions throttling (B) |
| Navoj | G 1/4 |
| Silicone-free | Yes |
| Telo | Nickel-plated brass |
| Tesnilo | NBR |
| Vrsta povezave | Plug-in connector |
| Za cevi [mm] | 6 |
| a/f [mm] | 10 |
| Max. obratovalni tlak [bar] | 10 |
| C [mm] | 24.0 |
| B [mm] | 50.8 |
| Max. temperaturno območje [°C] | 80 |