

Datum: 13.04.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si

(slika je simbolična)

Bimetalni termometer, zadaj, L1=100 mm / L2=80 mm, Ø 100

Kategorija: [Wika](#)
Šifra: **102804RIE**

Kratek opis

Bi-metallic thermometer, High quality design, Connection rear, for protective pipe L1=100 mm/L2=80 mm, Display range 0°C to 250°C
Applications: Extremely versatile design for use in machine, vessel, pipeline and plant construction as well as for heating systems.
A thermowell (removable with locking screw) is required.

Tehnične Specifikacije

Delovni tlak	Max. 25 bar (on thermowell)
Ohišje	CrNi steel
Okvir	CrNi steel
Položaj povezave	rear
Popravek prikaza	Trimming pointer
Povezava	Flush, with collar for thermowell, Ø 18 mm
Prednje steklo	Flat instrument glass
Primeren za termometer z dolžino	SR02 / SR12 / SR22
Stem	Ø 8 mm, CrNi steel
Stopnja rasti na območju skale - bar [bar]	2
Vrsta	52
Premer [mm]	100
Prikaz območja max. [°C]	250