

Datum: 31.05.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## **Bimetalni termometer, zadaj, L1=160 mm / L2=140 mm, Ø 63**

Kategorija: [Wika](#)  
Šifra: **102794RIE**

### **Kratek opis**

Bi-metallic thermometer, High quality design, Connection rear, for protective pipe L1=160 mm/L2=140 mm, Display range 0°C to 120°C  
Applications: Extremely versatile design for use in machine, vessel, pipeline and plant construction as well as for heating systems.  
A thermowell (removable with locking screw) is required.

### **Tehnične Specifikacije**

Delovni tlak	Max. 25 bar (on thermowell)
Ohišje	CrNi steel
Okvir	CrNi steel
Položaj povezave	rear
Popravek prikaza	Trimming pointer
Povezava	Flush, with collar for thermowell, Ø 18 mm
Prednje steklo	Flat instrument glass
Primeren za termometer z dolžino	SR03 / SR13 / SR23
Stem	Ø 8 mm, CrNi steel
Stopnja rasti na območju skale - bar [bar]	1
Vrsta	52
Premer [mm]	63
Prikaz območja max. [°C]	120