

Datum: 02.05.2025

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## **Bimetalni termometer, zadaj, L1=63 mm / L2=43 mm, Ø 63**

Kategorija: [Wika](#)  
Šifra: **102785RIE**

### **Kratek opis**

Bi-metallic thermometer, High quality design, Connection rear, for protective pipe L1=63 mm / L2=43 mm, Display range 0°C to 160°C

Applications: Extremely versatile design for use in machine, vessel, pipeline and plant construction as well as for heating systems.

A thermowell (removable with locking screw) is required.

### **Tehnične Specifikacije**

|                                            |                                            |
|--------------------------------------------|--------------------------------------------|
| Delovni tlak                               | Max. 25 bar (on thermowell)                |
| Ohišje                                     | CrNi steel                                 |
| Okvir                                      | CrNi steel                                 |
| Položaj povezave                           | rear                                       |
| Popravek prikaza                           | Trimming pointer                           |
| Povezava                                   | Flush, with collar for thermowell, Ø 18 mm |
| Prednje steklo                             | Flat instrument glass                      |
| Primeren za termometer z dolžino           | SR01 / SR11 / SR21                         |
| Stem                                       | Ø 8 mm, CrNi steel                         |
| Stopnja rasti na območju skale - bar [bar] | 1                                          |
| Vrsta                                      | 52                                         |
| Premjer [mm]                               | 63                                         |
| Prikaz območja max. [°C]                   | 160                                        |