TRG d.o.o.
Celovška cesta 150, 1000 Ljubljana

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.www.karcher-trg.si

Datum: 15.11.2026



(slika je simbolična)

Cev za odvod kond. »drukodrain«impulzno nadz.230 V/50 Hz

Kategorija: Drain for compressed air condensate »drukodrain«
Šifra: **101623RIE**

Kratek opis

Condensate drain line »drukodrain«, Pulse controlled, Voltage 230 V / 50 Hz, Operating pressure max. 16 bar
"
Ruggedly designed, cycle-controlled drain system for controlled drainage of compressed air condensate, proven thousands of times over and ready to use immediately. In contrast with conventional clock generators, the blowing and pause times of the »drukodrain« are not set in seconds or minutes but in bar or m³/min, depending on the pneumatic system installed upstream. Efficient and reliable operation is assured.
Benefits of »drukodrain«:
- Clock generator settings according to compressed air system:
""bar"" - for operating pressure
""m³/min"" - for compressor or dryer capacity
- Suitable for compressor / dryer capacities up to 20 m³/min
- Integrated dirt pan and G 1/2 ball valve
- 2 m connection cable with plug (230 V / 50 Hz) included
"

Tehnične Specifikacije

IP zaščita	IP 65
Max. obratovalni tlak [bar]	16
Napetost	230 V / 50 Hz