

Datum: 20.09.2024



Cilinder kratkega hodadelujoč v dveh smerehbatØ 32hod 25G 1/8

Kategorija: [Metalwork](#)
Šifra: **105920RIE**

(slika je simbolična)

Kratek opis

Short stroke cylinder, double-acting, Magnet, Piston Ø 32, Stroke 25, G 1/8, Working pressure max. 10 bar, Temp. -10 °C to 80 °C
Suitable for installation in limited spaces.
Supplied with magnet.
Suitable for filtered compressed air, lubricated (ensure continuity) or unlubricated.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Bat	Synthetic (acetal) resin
Batnica	C45 steel, hard chrome-plated
Batnica IT	M6
Cushioning	non-cushioned
Ffunkcija	double-acting
Gewinde Kolbenstange	female piston rod
Glava	Aluminium
Magnet	with magnet
Ovoj	C45 steel, hard chrome-plated
Povezava	G 1/8
Tesnilo batnice	NBR (additional charge for PU and FKM)
Min. nastavljeni tlak [bar]	0.6
Max. delovni tlak [bar]	10
Stroke [mm]	25
Bat Ø [mm]	32
Max. temperaturno območje [°C]	80