



Cilinder kratkega hodadelujoč v dveh smerehbatØ 50hod 10G 1/8

Kategorija: [Metalwork](#)
Šifra: **105931RIE**

(slika je simbolična)

Kratek opis

Short stroke cylinder, double-acting, Magnet, Piston Ø 50, Stroke 10, G 1/8, Working pressure max. 10 bar, Temp. -10 °C to 80 °C
Suitable for installation in limited spaces.
Supplied with magnet.
Suitable for filtered compressed air, lubricated (ensure continuity) or unlubricated.

Tehnične Specifikacije

| | |
|--------------------------------|--|
| Min. temperaturno območje [°C] | -10 |
| Bat | Synthetic (acetal) resin |
| Batnica | C45 steel, hard chrome-plated |
| Batnica IT | M8 |
| Cushioning | non-cushioned |
| Ffunkcija | double-acting |
| Gewinde Kolbenstange | female piston rod |
| Glava | Aluminium |
| Magnet | with magnet |
| Ovoj | C45 steel, hard chrome-plated |
| Povezava | G 1/8 |
| Tesnilo batnice | NBR (additional charge for PU and FKM) |
| Min. nastavljeni tlak [bar] | 0.4 |
| Max. delovni tlak [bar] | 10 |
| Stroke [mm] | 10 |
| Bat Ø [mm] | 50 |
| Max. temperaturno območje [°C] | 80 |