



## Cilinder kratkega hodadelujoč v dveh smerehbatØ 63hod 70G 1/8

Kategorija: [Metalwork](#)  
Šifra: **105943RIE**

(slika je simbolična)

### Kratek opis

Short stroke cylinder, double-acting, Magnet, Piston Ø 63, Stroke 70, G 1/8, Working pressure max. 10 bar, Temp. -10 °C to 80 °C  
Suitable for installation in limited spaces.  
Supplied with magnet.  
Suitable for filtered compressed air, lubricated (ensure continuity) or unlubricated.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Bat	Synthetic (acetal) resin
Batnica	C45 steel, hard chrome-plated
Batnica IT	M8
Cushioning	non-cushioned
Ffunkcija	double-acting
Gewinde Kolbenstange	female piston rod
Glava	Aluminium
Magnet	with magnet
Ovoj	C45 steel, hard chrome-plated
Povezava	G 1/8
Tesnilo batnice	NBR (additional charge for PU and FKM)
Min. nastavljeni tlak [bar]	0.4
Max. delovni tlak [bar]	10
Bat Ø [mm]	63
Stroke [mm]	70
Max. temperaturno območje [°C]	80