

Datum: 19.04.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si

Cilinder s kratkim hodom del. v dveh smereh bat Ø 100hod 40G 3/8

Kategorija: [Short-stroke cylinder, double-acting, with magnet](#)
Šifra: **115040RIE**

(slika je simbolična)

Kratek opis

Short stroke cylinder »ACQ« double-acting, Magnet, Piston Ø 100, Stroke 40, G 3/8, Working pressure 1-10 bar, Temp. -20°C to 70°C
Suitable for installation in limited spaces.
Supplied with magnet.
Short-stroke cylinders in two different versions:
»ACQ« Series, double-acting, Ø 12 to 100
»ASQ« Series, single-acting, Ø 12 to 63
Suitable for filtered, unlubricated or lubricated compressed air.
If lubrication is used, it must be continuous.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Bat	Aluminium
Batnica	Steel, thick-chromed
Batnica IT	M20x2.5
Cushioning	non-cushioned
Ffunkcija	double-acting
Gewinde Kolbenstange	female piston rod
Magnet	with magnet
Ovoj	Aluminium
Povezava	G 3/8
Serija	ACQ series
Tesnilo	NBR
Min. delovni tlak [bar]	1
Vrsta	3
Max. delovni tlak [bar]	10
Batnica Ø [mm]	32
Stroke [mm]	40
Max. temperaturno območje [°C]	70
Bat Ø [mm]	100