



## Cilinder s kratkim hodom del. v dveh smereh bat Ø 20hod 30M5x0,8

Kategorija: [Short-stroke cylinder, double-acting, with magnet](#)  
Šifra: **115072RIE**

(slika je simbolična)

### Kratek opis

Short stroke cylinder »ACQ« double-acting, Magnet, Piston Ø 20, Stroke 30, M5x0,8, Working pressure 1-10 bar, Temp. -20°C to 70°C  
Suitable for installation in limited spaces.  
Supplied with magnet.  
Short-stroke cylinders in two different versions:  
»ACQ« Series, double-acting, Ø 12 to 100  
»ASQ« Series, single-acting, Ø 12 to 63  
Suitable for filtered, unlubricated or lubricated compressed air.  
If lubrication is used, it must be continuous.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Bat	Aluminium
Batnica	Steel, thick-chromed
Batnica IT	M5x0.8
Cushioning	non-cushioned
Ffunkcija	double-acting
Gewinde Kolbenstange	female piston rod
Magnet	with magnet
Ovoj	Aluminium
Povezava	M5x0.8
Serija	ACQ series
Tesnilo	NBR
Min. delovni tlak [bar]	1
Vrsta	2
Batnica Ø [mm]	10
Max. delovni tlak [bar]	10
Bat Ø [mm]	20
Stroke [mm]	30
Max. temperaturno območje [°C]	70