

Datum: 04.06.2026

Cilinder s kratkim hodom del. v dveh smereh bat Ø 32hod 70G 1/8

Kategorija: [Short-stroke cylinder, double-acting, with magnet](#)
Šifra: **115107RIE**

(slika je simbolična)

Kratek opis

Short stroke cylinder »ACQ« double-acting, Magnet, Piston Ø 32, Stroke 70, G 1/8, Working pressure 1-10 bar, Temp. -20°C to 70°C
Suitable for installation in limited spaces.
Supplied with magnet.
Short-stroke cylinders in two different versions:
»ACQ« Series, double-acting, Ø 12 to 100
»ASQ« Series, single-acting, Ø 12 to 63
Suitable for filtered, unlubricated or lubricated compressed air.
If lubrication is used, it must be continuous.

Tehnične Specifikacije

| | |
|--------------------------------|----------------------|
| Min. temperaturno območje [°C] | -20 |
| Bat | Aluminium |
| Batnica | Steel, thick-chromed |
| Batnica IT | M8x1.25 |
| Cushioning | non-cushioned |
| Ffunkcija | double-acting |
| Gewinde Kolbenstange | female piston rod |
| Magnet | with magnet |
| Ovoj | Aluminium |
| Povezava | G 1/8 |
| Serija | ACQ series |
| Tesnilo | NBR |
| Min. delovni tlak [bar] | 1 |
| Vrsta | 3 |
| Max. delovni tlak [bar] | 10 |
| Batnica Ø [mm] | 16 |
| Bat Ø [mm] | 32 |
| Max. temperaturno območje [°C] | 70 |
| Stroke [mm] | 70 |