



(slika je simbolična)

## Cilinder z kratkim hodom, enosmerni, bat Ø 32, hod 30, G 1/8

Kategorija: [Short-stroke cylinder, single-acting, with magnet](#)  
Šifra: **115191RIE**

### Kratek opis

Short stroke cylinder »ASQ« single-acting, Magnet, Piston Ø 32, Stroke 30, G 1/8, Working pressure 2-10 bar, Temp. -20°C to 70°C

Suitable for installation in limited spaces.  
Supplied with magnet.

Short-stroke cylinders in two different versions:

»ACQ« Series, double-acting, Ø 12 to 100

»ASQ« Series, single-acting, Ø 12 to 63

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

### Tehnične Specifikacije

|                                |  |
|--------------------------------|--|
| Min. temperaturno območje [°C] | -20                                    |
| Bat                            | Aluminium                              |
| Batnica                        | Steel, thick-chromed                   |
| Batnica IT                     | M8x1.25                                |
| Cushioning                     | non-cushioned                          |
| Ffunkcija                      | single-acting                          |
| Gewinde Kolbenstange           | female piston rod                      |
| Magnet                         | with magnet                            |
| Ovoj                           | Aluminium                              |
| Povezava                       | G 1/8                                  |
| Serijska                       | ASQ series                             |
| Starting position              | pressureless in the retracted position |
| Tesnilo                        | NBR                                    |
| Min. delovni tlak [bar]        | 2                                      |
| Vrsta                          | 6                                      |
| Max. delovni tlak [bar]        | 10                                     |
| Batnica Ø [mm]                 | 16                                     |
| Stroke [mm]                    | 30                                     |
| Bat Ø [mm]                     | 32                                     |
| Max. temperaturno območje [°C] | 70                                     |