

Datum: 26.06.2026

(slika je simbolična)

Cilinder z kratkim hodom, enosmerni, bat Ø 63, hod 15, G 1/4

Kategorija: [Short-stroke cylinder, single-acting, with magnet](#)
Šifra: **115206RIE**

Kratek opis

Short stroke cylinder »ASQ« single-acting, Magnet, Piston Ø 63, Stroke 15, G 1/4, Working pressure 2-10 bar, Temp. -20°C to 70°C

Suitable for installation in limited spaces.

Supplied with magnet.

Short-stroke cylinders in two different versions:

»ACQ« Series, double-acting, Ø 12 to 100

»ASQ« Series, single-acting, Ø 12 to 63

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

Tehnične Specifikacije

| | |
|--------------------------------|--|
| Min. temperaturno območje [°C] | -20 |
| Bat | Aluminium |
| Batnica | Steel, thick-chromed |
| Batnica IT | M10x1.5 |
| Cushioning | non-cushioned |
| Ffunkcija | single-acting |
| Gewinde Kolbenstange | female piston rod |
| Magnet | with magnet |
| Ovoj | Aluminium |
| Povezava | G 1/4 |
| Serijska | ASQ series |
| Starting position | pressureless in the retracted position |
| Tesnilo | NBR |
| Min. delovni tlak [bar] | 2 |
| Vrsta | 6 |
| Max. delovni tlak [bar] | 10 |
| Stroke [mm] | 15 |
| Batnica Ø [mm] | 20 |
| Bat Ø [mm] | 63 |
| Max. temperaturno območje [°C] | 70 |