



(slika je simbolična)

Coaxial valve pneumat. actuated, single-acting NC, FKM, Rp 1/2

Kategorija: [Coaxial valve, single-acting - spring to close,FKM](#)
Šifra: **103736RIE**

Kratek opis

Coaxial valve pneumat. actuated, single-acting, NC, nickel-plated brass, Temp. -20°C to 150°C, Control pressure 4.2-8 bar, Rp 1/2

2/2-way coaxial valves, specially designed for automated industrial plant engineering.

A low-price, compact, space-saving and reliable alternative to ball valves with a pneumatic rotary actuator.

These valves have a full bore and - owing to the optimised design - only minimal flow losses.

They are controlled by means of filtered compressed air.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Navoj	Rp 1/2
Notranji deli	Nickel-plated brass
Ohišje	Nickel-plated brass
Povezava	NAMUR interface, direct: 2 x G 1/8
Različica	single-acting - spring to close
Tesnilo	FKM
Vgradni položaj	Any
Vzmet	Stainless steel
Min. vodeni tlak [bar]	4.2
Max. vodeni tlak [bar]	8
Max. obratovalni tlak [bar]	10
DN	15
H [mm]	51.7
L [mm]	112.0
Max. delovna temperatura [°C]	150