

Datum: 12.06.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si

(slika je simbolična)

Dekabon cev, cev-O: 12x8.13 mm, črna, rola 25 m

Kategorija: [Dekabon tubes](#)
Šifra: **141366RIE**

Kratek opis

Dekabon tube, Tube-Ø: 12x8.13 mm, PN at 23 °C max. 24.5 bar, Temp. -40 °C to 80 °C, black, Roll of 25 m

Dekabon tubing, which combines the advantages of metal and plastic tubing.

Bending the very light tubing is possible without special tools. Good resistance against corrosion and various chemicals. The interior tube remains dry due to a film/aluminium barrier and can be laid in the ground without additional protection.

Connection is possible with push-in connectors (additional self testing) and cutting ring fittings (amplification sleeve recommended).

Areas of application:

- pneumatic measurement and control lines in very wet or moist environments
- air and gas sampling
- aggressive environments (corrosion)
- The interior surface is best suited for air

Tehnične Specifikacije

Min. temperaturno območje [°C]	-40
Zračnico	Aluminium
Zunanji pokrov	Polyethylene
I.D. cevi [mm]	8.13
O.D. cevi [mm]	12
Max. obratovalni tlak pri 23 °C [bar]	24
Dolžina koluta [m]	25
Min. polmer upogibanja [mm]	40
Max. temperaturno območje [°C]	80