

Datum: 31.08.2025

TRG d.o.o. Celovška cesta 150, 1000 Ljubljana

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.www.karcher-trg.si



<u>Detektor uhajanja, vključno z dodatki v praktičnem primeru</u>

Kategorija: <u>Leak detector</u> Šifra: **134679RIE**

(slika je simbolična)

Kratek opis

Leak detector incl. accessories in a practical case, Ultrasonics measurement technology, Working temperature 0 °C to 40 °C PRINCIPLE:

High and avoidable energy costs are caused every year by leaks in compressed air and gas installations.

Noise in the ultrasonic range is caused by gases escaping from leaks. These ultrasonic sounds are not audible to the human ear.

The LS 200 leak detector picks up even smallest leaks from a distance of several metres. How? It transformst he inaudible ultrasonic sounds into a frequency that can be detected visually on the display and acoustically with the aid oft he soundproof headphones.

The LS 200 is the further development of the proven LS 100 and features a significantly refined sensor technology that effectively improves the detection of leaks. The display is optimized by enlarging the display. The integrated laser pointer is used for target bearing. This allows leaks tob e located precisely.

The specially designed bell achieves a better bundling of the sound waves. This horn achts like a directional microphone. Disturbing backgrounds noises, for example those that occur during operation, are suppressed or faded out. This makes it easier to locate leaks even in areas that are difficult to access.

APPLICATIONS:

Leak detection in compressed air, gas, steam and vacuum systems. Not suitable for helium.

ADVANTAGES:

- Simple and fast measurement even from a distance of several meters.
- Measurements can be carried out during operation without impairing it.
- Short payback time oft he device due to high cost savings.
- Loud background noise does not affect the quality oft he measurements in any way, since the acoustic frequency works in the ultrasonic range.
- Safe and easy handling. CONNECTION:
- Mains adapter socket for external charging unit
- · 3.5-mm jack plug for headphones

SCOPE OF DELIVERY IN A PRACTICAL SUITCASE SET:

- Leak detector with ultrasonic sensor
- Acoustic trumpet
- Focus tube with focus tip
- Soundproof, ergonomic headphones
- Power supply unit/charger
- Carrying case

Tehnične Specifikacije

Min. temperatura skladiščenja

1001

Čas polnjenja [Stunden] Approx.

Laser kot optično orodje

,

Napajanje

Obratovalni čas

Delovna frekvenca

Max. delovna temperatura

Opis

[°C] Max. temperatura

skladiščenja [°C]

-10

Approx. 1.5

Wave length: 645...660 nm, Output power: <1 mW

Lithium-ion battery with high capacity, external recharger

Approx. 10 hours

Leak detection device incl. accessories in a carrying case

40 kHz ± 2 kHz

40

50