

Datum: 05.04.2026



(slika je simbolična)

## Dušilna ploščica za NAMUR ventil, 5-potni, imbus vijak

Kategorija: [Flow regulators for NAMUR valves](#)  
Šifra: **103665RIE**

### Kratek opis

Throttle plate for NAMUR valves, Anodised aluminium, Temp. -20 °C to 70 °C, Working pressure 0.5 - 10 bar, 5-way, Knurled screw

Block-form flow regulator as an intermediate plate between the control valve and actuator acc. to the G 1/4 NAMUR standard.

3/2-way flow regulators:

Independent regulation of the forward and return strokes of a single-acting pneumatic actuator.

5/2-way flow regulators:

Regulation of the forward and return strokes of a double-acting pneumatic actuator.

### Tehnične Specifikacije

|                               |                                          |
|-------------------------------|------------------------------------------|
| Min. delovna temperatura [°C] | -20                                      |
| Delovanje                     | Knurled screw                            |
| Ohišje                        | Aluminium anodised                       |
| Srednje                       | Air, neutral gases (filtered)            |
| Tesnilo                       | NBR                                      |
| Min. delovni tlak [bar]       | 0.5                                      |
| Obseg dobave                  | 1 coding pin, 2 O-rings, 2 fixing screws |
| DN                            | 5                                        |
| Ffunkcija                     | 5-way                                    |
| Max. delovni tlak [bar]       | 10                                       |
| Max. delovna temperatura [°C] | 70                                       |
| Pretok [l/min]                | 650                                      |