



(slika je simbolična)

Dvojna Hitre spojke I.D. 7.2, G 1/2 zunanji navoj, »R26EMS«

Kategorija: [Distributor, 2 quick disconnect coupl. DN 7.2, ET](#)
Šifra: **117926RIE**

Kratek opis

Distributor with 2 quick-connect couplings I.D. 7.2, »R26EMS«, Bright brass, G 1/2 ET, Operating pressure 0 - 35 bar
2-way distributor pieces made of brass with a bare metal surface, pre-assembled with quick disconnect coupling DN 7.2.
Available with threaded connection inside or outside.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Ohišje	Brass with a bare metal surface
Povezava	G 1/2 ET
Sestava distributerja	Brass with a bare metal surface, G 1/2 IT DN 7.2, brass with a bare metal surface, G 1/2 ET
Spojke	Industrial adhesives, medium strength
Tesnilo	Industrial adhesives, medium strength
Varovaka	Industrial adhesives, medium strength
Max. obratovalni tlak [bar]	35
Višina [mm]	89.0
Premer [mm]	91.0
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100