



(slika je simbolična)

Dvojna Hitre spojke I.D. 7.2, G 3/8 zunanji navoj, »R26EMS«

Kategorija: [Distributor, 2 quick disconnect coupl. DN 7.2, ET](#)
Šifra: **117925RIE**

Kratek opis

Distributor with 2 quick-connect couplings I.D. 7.2, »R26EMS«, Bright brass, G 3/8 ET, Operating pressure 0 - 35 bar
2-way distributor pieces made of brass with a bare metal surface, pre-assembled with quick disconnect coupling DN 7.2.
Available with threaded connection inside or outside.

Tehnične Specifikacije

| | |
|------------------------------|--|
| Min. sobna temperatura [°C] | -20 |
| Min. temperatura medija [°C] | -20 |
| Ohišje | Brass with a bare metal surface |
| Povezava | G 3/8 ET |
| Sestava distributerja | Brass with a bare metal surface, G 3/8 IT DN 7.2, brass with a bare metal surface, G 3/8 ET |
| Spojke | Industrial adhesives, medium strength |
| Tesnilo | Industrial adhesives, medium strength |
| Varovaka | Industrial adhesives, medium strength |
| Max. obratovalni tlak [bar] | 35 |
| Višina [mm] | 85.0 |
| Premer [mm] | 90.0 |
| Max. sobna temperatura [°C] | 100 |
| Max. temperatura medija [°C] | 100 |