

Datum: 31.05.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



Dvojni nav. priklj. 245, reduciran, R 1 1/2 Z.N., R 1 Z.N.

Kategorija: [Hexagon nipple 245, reducing, male/male, black](#)
Šifra: **133758RIE**

(slika je simbolična)

Kratek opis

Double threaded nipple 245, reducing, R 1 1/2 ET, R 1 ET, black malleable iron fitting, operating temp. -20 °C to 300 °C, ISO 7-1

According to DIN EN 10242 (previously 2950).

Malleable iron cast fittings in black steel, non-galvanized, is the classic fitting series in connection series in piping construction. Our malleable iron cast fittings are characterized by high mechanical strength and standardized fitting technology.

Working minimal temperature = -20 °C, 25 bar.

Working pressure for temperature range from -20 °C to 120 °C: 25 bar.

Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Tehnične Specifikacije

| | |
|--------------------------------|---|
| Min. temperaturno območje [°C] | -20 |
| Material | Black malleable iron B350-10, design symbol A |
| Navoj 1 | R 1 1/2 |
| Navoj 2 | R 1 |
| Površina | Black |
| Standardni navoj | acc. ISO 7-1 |
| Max. temperaturno območje [°C] | 300 |