

Datum: 21.04.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



Dvojni nav. priklj. 245, reduciran, R 1 1/4 Z.N., R 3/4 Z.N.

Kategorija: [Hexagon nipple 245, reducing, male/male, black](#)
Šifra: **133756RIE**

(slika je simbolična)

Kratek opis

Double threaded nipple 245, red., R 1 1/4 ET, R 3/4 ET, black malleable iron fitting, oper. temp. -20 °C to 300 °C, ISO 7-1 According to DIN EN 10242 (previously 2950).

Malleable iron cast fittings in black steel, non-galvanized, is the classic fitting series in connection series in piping construction. Our malleable iron cast fittings are characterized by high mechanical strength and standardized fitting technology.

Working minimal temperature = -20 °C, 25 bar.

Working pressure for temperature range from -20 °C to 120 °C: 25 bar.

Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Material	Black malleable iron B350-10, design symbol A
Navoj 1	R 1 1/4
Navoj 2	R 3/4
Površina	Black
Standardni navoj	acc. ISO 7-1
Max. temperaturno območje [°C]	300