TRG d.o.o.
Celovška cesta 150, 1000 Ljubljana

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.www.karcher-trg.si

Datum: 28.11.2026



(slika je simbolična)

Dvojni nav. priklj. 245, Z.N./Z.N.,reduciran,R 1 1/2,R 1

Kategorija: Hexagon nipple 245, reducing, male/male
Šifra: **113097RIE**

Kratek opis

Double threaded nipple 245, ET/ET, red., R 1 1/2, R 1, oper. temp. -20 °C to 300 °C, black malleable cast iron, Hot-dip galvanised
"
Acc. to DIN EN 10242 (formerly DIN 2950)
The classic - and the most popular - screw fitting series for pipe construction.
These fittings are characterized by their high mechanical strength and surface quality to DIN 2444.
They are completely coated with a layer of pure zinc and are therefore suitable for drinking water

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Material	Black malleable iron B350-10, design symbol A
Navoj 1	R 1 1/2
Navoj 2	R 1
Površina	Hot dip galvanised
Standardni navoj	acc. ISO 7-1
Max. temperaturno območje [°C]	300