

Datum: 13.04.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Dvojni nav. priklj. 245, Z.N./Z.N.,reduciran,R 1/2,R 3/8

Kategorija: [Hexagon nipple 245, reducing, male/male](#)  
Šifra: **113090RIE**

### Kratek opis

Double threaded nipple 245, ET/ET, red., R 1/2, R 3/8, oper. temp. -20 °C to 300 °C, black malleable cast iron, Hot-dip galvanised

"  
Acc. to DIN EN 10242 (formerly DIN 2950)  
The classic - and the most popular - screw fitting series for pipe construction.  
These fittings are characterized by their high mechanical strength and surface quality to DIN 2444.  
They are completely coated with a layer of pure zinc and are therefore suitable for drinking water

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Material	Black malleable iron B350-10, design symbol A
Navoj 1	R 1/2
Navoj 2	R 3/8
Površina	Hot dip galvanised
Standardni navoj	acc. ISO 7-1
Max. temperaturno območje [°C]	300