

Datum: 16.06.2026



(slika je simbolična)

[El. priključek \(večpolni 25-pol, IP 65\), vtičnica IP 67 1 m kabel](#)

Kategorija: [Metalwork](#)
Šifra: **106700RIE**

Kratek opis

Electrical connection (multipole 25-pole, IP 65), Socket IP 67, 25-pole, with 1 m cable

These compact valve terminals, with a maximum flow rate of 800 NI/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates.

Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.

Suitable for filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.

Monostable (non-latching) version of manual control also available on request.

The operating pressure is based on the installed input plates.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
IP zaščita	IP 65
Opis	IP 67 connector, 25-pin, with 1 m cable
Poskusno	Max. 16 (e.g. 16 spring return valves)
Ročno upravljanje	latching
Vhodna moč	0.6 W per pilot
Max. temperaturno območje [°C]	60