



(slika je simbolična)

## **Elektronsko tlačno stikalo, digitalni, M12x1, G 1/4, 0-60 bar**

Kategorija: [Wika](#)  
Šifra: **103081RIE**

### **Kratek opis**

Electr. pressure switch, Digital display, M12x1, 4-pole, Measuring material temp. -20°C to 85°C, G 1/4, Measurement range 0-60 bar  
Electronic pressure switch with digital display, made of stainless steel, for monitoring and measuring pressures in liquids, gases or compressed air.  
Applications: Machine tools, compressors and pumps, hydraulic and pneumatic systems, machinery in general, factory automation.  
Customisable switching functions: Switching / switch-back point or window function, switching delay times, NO and NC functions, min. / max. memory. Password protection for maximum security.  
The display and case can be turned 300° for mounting in any position.  
Three large keys for intuitive operation with an easy-to-read display conforming to VDMA Standard 24574-1.  
Optional on request: Pressure switch with additional analog signal 4 - 20 mA, DC 0 - 10 V and 5-pin plug.

### **Tehnične Specifikacije**

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Deli v kontaktu z medijem	CrNi steel circular plug-in connector M12 x 1, 4-pin
Električni priključek	IP 65 and IP 67 (M12x1)
IP zaščita	DC 15 - 35 V
Napajanje	CrNi steel
Ohišje	G 1/4
Povezava	G 1/4
Procesni priključek	G 1/4
Natančnost izhodni signal	1% of span 2 switching outputs
Merilno območje max. bar	60
Max. sobna temperatura [°C]	80
Max. temperatura medija [°C]	85