



(slika je simbolična)

## Filter reg.»FUTURA« Kov. Vel. 4, G3/4, 0.5-16 bar, Avt.

Kategorija: [Filter regulator with metal bowl and sight glass](#)Šifra: **151867RIE**

### Kratek opis

Filter regulator »FUTURA« with metal container, Viewing tube, Pressure gauge, 5 µm, Size 4, G 3/4, Control range 0.5-16 bar, Fully  
Filter regulators with excellent flow rates in modern design. The regulator knob can be latched and locked.

### Tehnične Specifikacije

|                                |   |
|--------------------------------|---|
| Min. temperaturno območje [°C] | -10   |
| Element filtra                 | Cellpor (PE)  |
| Membrane                       | NBR   |
| Merjenje pretoka               | At P <sub>1</sub> = 10 bar, P <sub>2</sub> = 6.3 bar and pressure drop Δ <sub>p</sub> = 1 bar |
| Navoj                          | G 3/4   |
| Odtok kondenzata               | Fully-automatic   |
| Ohišje                         | PA66 GF60   |
| Poraba zraka                   | Yes   |
| Posoda                         | Metal container with viewing tube   |
| Priključni navoj               | Material: Die-cast zinc   |
| Serijska                       | FUTURA  |
| Srednje                        | Compressed air, neutral gases   |
| Tesnilo                        | NBR   |
| Min. krmilno območje [bar]     | 0.5   |
| Max. notranja poraba zraka     | 1.5 l/min (depending on secondary pressure)   |
| Min. vhodni tlak [bar]         | 1.5   |
| Velikost                       | 4   |
| Rang filtra [µm]               | 5   |
| Max. krmilno območje [bar]     | 16  |
| Max. vhodni tlak [bar]         | 16  |
| Zaslon manometra max. [bar]    | 25  |
| Max. temperaturno območje [°C] | 50  |
| A [mm]                         | 85.0  |
| C [mm]                         | 137.0   |
| B [mm]                         | 343.0   |
| Pretok [l/min]                 | 13000   |