

Datum: 18.04.2026



(slika je simbolična)

Filter reg.»FUTURA« Kov. Vel.2, G 3/8, 0.5-8 bar Pol avto.

Kategorija: [Filter regulator with metal bowl and sight glass](#)Šifra: **139487RIE**

Kratek opis

Filter regulator »FUTURA«, with metal container, Viewing tube, Pressure gauge, 5 µm, Size 2, G 3/8, Control range 0.5-8 bar, Semi
Filter regulators with excellent flow rates in modern design. The regulator knob can be latched and locked.

Tehnične Specifikacije

| | |
|--------------------------------|---|
| Min. temperaturno območje [°C] | -10 |
| Element filtra Membrane | Cellpor (PE) NBR |
| Merjenje pretoka | At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj | G 3/8 |
| Odtok kondenzata | Semi-automatic |
| Ohišje | PA66 GF60 |
| Posoda | Metal container with viewing tube |
| Priključni navoj | Material: Die-cast zinc |
| Serijska | FUTURA |
| Srednje | Compressed air, neutral gases |
| Tesnilo | NBR |
| Min. krmilno območje [bar] | 0.5 |
| Min. vhodni tlak [bar] | 1.5 |
| Velikost | 2 |
| Rang filtra [µm] | 5 |
| Max. krmilno območje [bar] | 8 |
| Zaslon manometra max. [bar] | 10 |
| Max. vhodni tlak [bar] | 16 |
| Max. temperaturno območje [°C] | 50 |
| A [mm] | 63.0 |
| C [mm] | 110.0 |
| B [mm] | 261.0 |
| Pretok [l/min] | 4500 |