

Datum: 18.04.2026



(slika je simbolična)

Filter reg.»FUTURA« Kov. Vel.4, G 3/4, 0.1-2 bar Pol avto.

Kategorija: [Filter regulator with metal bowl and sight glass](#)Šifra: **151827RIE**

Kratek opis

Filter regulator »FUTURA«, with metal container, Viewing tube, Pressure gauge, 5 µm, Size 4, G 3/4, Control range 0.1-2 bar, Semi
Filter regulators with excellent flow rates in modern design. The regulator knob can be latched and locked.

Tehnične Specifikacije

| | |
|--------------------------------|---|
| Min. temperaturno območje [°C] | -10 |
| Element filtra | Cellpor (PE) |
| Membrane | NBR |
| Merjenje pretoka | At P ₁ = 10 bar, P ₂ = 6.3 bar and pressure drop Δ _p = 1 bar |
| Navoj | G 3/4 |
| Odtok kondenzata | Semi-automatic |
| Ohišje | PA66 GF60 |
| Poraba zraka | Yes |
| Posoda | Metal container with viewing tube |
| Priključni navoj | Material: Die-cast zinc |
| Serija | FUTURA |
| Srednje | Compressed air, neutral gases |
| Tesnilo | NBR |
| Min. krmilno območje [bar] | 0.1 |
| Max. notranja poraba zraka | 1.5 l/min (depending on secondary pressure) |
| Min. vhodni tlak [bar] | 1.5 |
| Max. krmilno območje [bar] | 2 |
| Zaslon manometra max. [bar] | 2.5 |
| Velikost | 4 |
| Rang filtra [µm] | 5 |
| Max. vhodni tlak [bar] | 16 |
| Max. temperaturno območje [°C] | 50 |
| A [mm] | 85.0 |
| C [mm] | 137.0 |
| B [mm] | 326.0 |
| Pretok [l/min] | 13000 |