



(slika je simbolična)

Filter reg.»FUTURA« PC, Vel. 4, G 1, 0.2-4 bar, Pol avto.

Kategorija: [Filter regulator, polycarbonate bowl, bowl guard](#)
Šifra: **151781RIE**

Kratek opis

Filter regulator »FUTURA«, with PC container, Protective cage, Pressure gauge, 5 µm, Size 4, G 1, Control range 0.2-4 bar, Semi

Filter regulators with excellent flow rates in modern design. The regulator knob can be latched and locked.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Cellpor (PE)
Membrane	NBR
Merjenje pretoka	At P ₁ = 10 bar, P ₂ = 6.3 bar and pressure drop Δ _p = 1 bar
Navoj	G 1
Odtok kondenzata	Semi-automatic
Ohišje	PA66 GF60
Poraba zraka	Yes
Posoda	Polycarbonate container with protective cage
Priključni navoj	Material: Die-cast zinc
Serijska	FUTURA
Srednje	Compressed air, neutral gases
Tesnilo	NBR
Min. krmilno območje [bar]	0.2
Max. notranja poraba zraka	1.5 l/min (depending on secondary pressure)
Min. vhodni tlak [bar]	1.5
Max. krmilno območje [bar]	4
Velikost	4
Rang filtra [µm]	5
Zaslon manometra max. [bar]	6
Max. vhodni tlak [bar]	16
Max. temperaturno območje [°C]	50
A [mm]	85.0
C [mm]	137.0
B [mm]	326.0
Pretok [l/min]	13000