



(slika je simbolična)

Filter reg.»FUTURA« PC, Vel.1, G 1/4, 0.5-16 bar, Pol avto.

Kategorija: [Filter regulator, polycarbonate bowl, bowl guard](#)
Šifra: **151768RIE**

Kratek opis

Filter regulator »FUTURA«, with PC container, Protective cage, Pressure gauge, 5 µm, Size 1, G 1/4, Control range 0.5-16 bar, Semi
Filter regulators with excellent flow rates in modern design. The regulator knob can be latched and locked.

Tehnične Specifikacije

| | |
|--------------------------------|---|
| Min. temperaturno območje [°C] | -10 |
| Element filtra Membrane | Cellpor (PE) NBR |
| Merjenje pretoka | At P ₁ = 10 bar, P ₂ = 6.3 bar and pressure drop Δ _p = 1 bar |
| Navoj | G 1/4 |
| Odtok kondenzata | Semi-automatic |
| Ohišje | PA66 GF60 |
| Posoda | Polycarbonate container with protective cage |
| Priključni navoj | Material: Die-cast zinc |
| Serijska | FUTURA |
| Srednje | Compressed air, neutral gases |
| Tesnilo | NBR |
| Min. krmilno območje [bar] | 0.5 |
| Velikost | 1 |
| Min. vhodni tlak [bar] | 1.5 |
| Rang filtra [µm] | 5 |
| Max. krmilno območje [bar] | 16 |
| Max. vhodni tlak [bar] | 16 |
| Zaslona manometra max. [bar] | 25 |
| Max. temperaturno območje [°C] | 50 |
| A [mm] | 52.0 |
| C [mm] | 96.0 |
| B [mm] | 226.0 |
| Pretok [l/min] | 2000 |