



(slika je simbolična)

Filter reg.»FUTURA« PC, Vel.1, G 3/8, 0.5-16 bar, Pol avto.

Kategorija: [Filter regulator, polycarbonate bowl, bowl guard](#)Šifra: **151773RIE**

Kratek opis

Filter regulator »FUTURA«, with PC container, Protective cage, Pressure gauge, 5 µm, Size 1, G 3/8, Control range 0.5-16 bar, Semi
Filter regulators with excellent flow rates in modern design.
The regulator knob can be latched and locked.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra Membrane	Cellpor (PE) NBR
Merjenje pretoka	At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 3/8
Odtok kondenzata	Semi-automatic
Ohišje	PA66 GF60
Posoda	Polycarbonate container with protective cage
Priključni navoj	Material: Die-cast zinc
Serijska	FUTURA
Srednje	Compressed air, neutral gases
Tesnilo	NBR
Min. krmilno območje [bar]	0.5
Velikost	1
Min. vhodni tlak [bar]	1.5
Rang filtra [µm]	5
Max. krmilno območje [bar]	16
Max. vhodni tlak [bar]	16
Zaslona manometra max. [bar]	25
Max. temperaturno območje [°C]	50
A [mm]	52.0
C [mm]	96.0
B [mm]	226.0
Pretok [l/min]	2500