



(slika je simbolična)

Filter reg. »multifix«5 µmVel. 3G 3/4, 0.5 - 16 bar

Kategorija: [Filter regulator with polycarbonate bowl](#)Šifra: **100483RIE**

Kratek opis

Filter regulator »multifix«, PC container, press. gauge, 5 µm, Size 3, G 3/4, Input pressure max. 16 bar, Control range 0.5-16 bar

Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator.

The pressure setting can be locked by pushing the button down.

Tehnične Specifikacije

| | |
|------------------------------|---|
| Merjenje pretoka | At $P_1 = 10$ bar, $P_2 = 6,3$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj | G 3/4 |
| Odtok kondenzata | Semi-automatic |
| Ohišje | Die-cast zinc |
| Posoda | Polycarbonate container |
| Serija | multifix |
| Tesnilo | NBR |
| Vzmet pokrova motorja | POM-brass |
| Min. krmilno območje [bar] | 0.5 |
| Velikost | 3 |
| Rang filtra [µm] | 5 |
| Max. krmilno območje [bar] | 16 |
| Max. vhodni tlak [bar] | 16 |
| DN | 20 |
| Zaslon manometra max. [bar] | 25 |
| Max. sobna temperatura [°C] | 60 |
| Max. temperatura medija [°C] | 60 |
| A [mm] | 68.8 |
| C [mm] | 99.0 |
| D [mm] | 147.3 |
| B [mm] | 246.3 |
| Pretok [l/min] | 6700 |