



(slika je simbolična)

Filter reg. »Stinard«Kov. pos.5 µmVel.1,G 1/4

Kategorija: [Filter regulator with metal bowl](#)
Šifra: **100934RIE**

Kratek opis

Filter regulator »Standard«, Metal container and pressure gauge, 5 µm, Size 1, G 1/4, Input pressure max. 25 bar, 0.5 - 16 bar

Reversible diaphragm pressure regulators, independent of inlet pressure, with selfrelieving design, combined with a centrifugal separator.

Tehnične Specifikacije

| | |
|------------------------------|--|
| Merjenje pretoka | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj | G 1/4 |
| Odtok kondenzata | Manuel |
| Ohišje | Die-cast zinc, painted silver |
| Posoda | Metal container |
| Serija | Standard |
| Tesnilo | NBR |
| Min. krmilno območje [bar] | 0.5 |
| Velikost | 1 |
| Rang filtra [µm] | 5 |
| DN | 8 |
| Max. krmilno območje [bar] | 16 |
| Max. vhodni tlak [bar] | 25 |
| Zaslon manometra max. [bar] | 25 |
| A [mm] | 54.0 |
| Max. sobna temperatura [°C] | 60 |
| Max. temperatura medija [°C] | 60 |
| F [mm] | 62.0 |
| C [mm] | 106.5 |
| D [mm] | 133.5 |
| Pretok [l/min] | 900 |