



(slika je simbolična)

## Filter reg. »Stinard«Kov. pos.5 µmVel.1,G 3/8

Kategorija: [Filter regulator with metal bowl](#)  
Šifra: **100935RIE**

### Kratek opis

Filter regulator »Standard«, Metal container and pressure gauge, 5 µm, Size 1, G 3/8, Input pressure max. 25 bar, 0.5 - 16 bar  
Reversible diaphragm pressure regulators, independent of inlet pressure, with selfrelieving design, combined with a centrifugal separator.

### Tehnične Specifikacije

|                              |  |
|------------------------------|--|
| Merjenje pretoka             | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj                        | G 3/8  |
| Odtok kondenzata             | Manuel   |
| Ohišje                       | Die-cast zinc, painted silver  |
| Posoda                       | Metal container  |
| Serija                       | Standard   |
| Tesnilo                      | NBR  |
| Min. krmilno območje [bar]   | 0.5  |
| Velikost                     | 1  |
| Rang filtra [µm]             | 5  |
| DN                           | 8  |
| Max. krmilno območje [bar]   | 16   |
| Max. vhodni tlak [bar]       | 25   |
| Zaslon manometra max. [bar]  | 25   |
| A [mm]                       | 54.0   |
| Max. sobna temperatura [°C]  | 60   |
| Max. temperatura medija [°C] | 60   |
| F [mm]                       | 62.0   |
| C [mm]                       | 106.5  |
| D [mm]                       | 133.5  |
| Pretok [l/min]               | 900  |