



(slika je simbolična)

Filter reg. »Stinard«PC zbir.40 µmVel.4,G 3/4

Kategorija: [Filter regulator with polycarbonate bowl](#)
Šifra: **100926RIE**

Kratek opis

Filter regulator »Standard« PC container, press. gauge, 40 µm, Size 4, G 3/4, Input pressure max. 16 bar, Control range 0.5-10 bar
Reversible diaphragm pressure regulators, independent of inlet pressure, with selfrelieving design, combined with a centrifugal separator.

Tehnične Specifikacije

| | |
|------------------------------|--|
| Merjenje pretoka | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj | G 3/4 |
| Odtok kondenzata | Semi-automatic |
| Ohišje | Aluminium, painted silver |
| Posoda | Polycarbonate container |
| Serija | Standard |
| Tesnilo | NBR |
| Min. krmilno območje [bar] | 0.5 |
| Velikost | 4 |
| Max. krmilno območje [bar] | 10 |
| Max. vhodni tlak [bar] | 16 |
| Zaslon manometra max. [bar] | 16 |
| DN | 25 |
| Rang filtra [µm] | 40 |
| Max. sobna temperatura [°C] | 60 |
| Max. temperatura medija [°C] | 60 |
| A [mm] | 125.0 |
| F [mm] | 145.0 |
| C [mm] | 190.6 |
| D [mm] | 261.4 |
| Pretok [l/min] | 7000 |