

Datum: 02.05.2025



(slika je simbolična)

## **Filter regulator »G«, PC zbiralnik, 5 µm, Velikost 300, G 1/4**

Kategorija: [Filter regulator with PC bowl, bowl guard](#)Šifra: **116356RIE**

### **Kratek opis**

Filter regulator »G«, with PC container, Protective cage, Mounting bracket, 5 µm, Size 300, G 1/4, Input pressure max. 10 bar  
Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator.  
The pressure setting can be locked by pushing the button down.

### **Tehnične Specifikacije**

|                              |                                                                      |
|------------------------------|----------------------------------------------------------------------|
| Merjenje pretoka             | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj                        | G 1/4                                                                |
| Odtok kondenzata             | Semi-automatic                                                       |
| Ohišje                       | Die-cast aluminium                                                   |
| Posoda                       | Polycarbonate container with protective cage                         |
| Serija                       | G                                                                    |
| Tesnilo                      | NBR                                                                  |
| Vzmet pokrova motorja        | POM                                                                  |
| Min. krmilno območje [bar]   | 1.5                                                                  |
| Rang filtra [µm]             | 5                                                                    |
| Max. krmilno območje [bar]   | 9                                                                    |
| Max. vhodni tlak [bar]       | 10                                                                   |
| A [mm]                       | 51.0                                                                 |
| Max. sobna temperatura [°C]  | 70                                                                   |
| Max. temperatura medija [°C] | 70                                                                   |
| C [mm]                       | 82.5                                                                 |
| D [mm]                       | 143.0                                                                |
| B [mm]                       | 225.5                                                                |
| Velikost                     | 300                                                                  |
| Pretok [l/min]               | 1450                                                                 |