

Datum: 01.07.2026



(slika je simbolična)

Filter regulator »G«, PC zbiralnik, 5 µm, Velikost 400, G 3/8

Kategorija: [Filter regulator with PC bowl, bowl guard](#)Šifra: **116363RIE**

Kratek opis

Filter regulator »G«, with PC container, Protective cage, Mounting bracket, 5 µm, Size 400, G 3/8, Input pressure max. 10 bar
Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator.
The pressure setting can be locked by pushing the button down.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 3/8
Odtok kondenzata	Fully-automatic
Ohišje	Die-cast aluminium
Posoda	Polycarbonate container with protective cage
Serija	G
Tesnilo	NBR
Vzmet pokrova motorja	POM
Min. krmilno območje [bar]	1.5
Rang filtra [µm]	5
Max. krmilno območje [bar]	9
Max. vhodni tlak [bar]	10
A [mm]	68.0
Max. sobna temperatura [°C]	70
Max. temperatura medija [°C]	70
C [mm]	104.0
D [mm]	166.5
B [mm]	270.5
Velikost	400
Pretok [l/min]	3750